

Decolorising Shaker

This Decolorising Shaker which swings up and down with little swing amplitude. Frequency adjustable. it's used for fixing of running gel spectral band, rocking of Coomassie blue and decolorization and fixing of silver nitrate staining, etc. It's used for development and fixation of X-ray film, further treatment cellulose membrane after electrophoretic migration, molecular hybridization, cell culture and blood mixing.

Technical Data

Rocking Speed: 0-25 rpm
Rocking angle: ±25°
Working plate size: 250×200mm
External dimention: 420×200×200mm
Voltage: AC 80-230V (50/60Hz)
N.W.: 2.5Kg

Order information

Cat.No.	Part.No.	Specification
8011259	TMM-5DS	Decolorising Shaker



Feature
Rocking angle adjustable
Speed adjustable
Time setting



Large LCD show the all the parameter

TRM-7S digital Roller Mixer

TRM-7S digital Roller Mixer provides a gentle but highly efficient rocking and rolling motions, ideal for mixing blood samples, viscous substances and liquid-solid suspensions. Used in a variety applications, prevention of blood coagulation and immune precipitation etc.

Technical Data:

Speed : (adjustable,) 10-99 rpm +-10%
Motion : (Simultaneous roll&tilt +-5%)
Operating Temp :4°C-40°C
Electrical : 80-230V,50-60Hz 50W

Feature

Rocking and rolling motions for complete mixing
Display show the speed and time
Speed range of 10-99rpm
Seven roller design with small footprint and easy clean
Digital setting speed and time



Time showing Speed showing

Order information

Cat.No.	Part.No.	Specification
8011560	TM-7S	Roller Mixer(digital showing)

Mivot mixer

The Vortex mixer widely used in life science, physical and chemical analysis fields, for vigorous re-suspension of cells or chemical pellets in tubes up to 15 ml.

Features

Touch and continuous operations
Mini and compact appearance , powerful function , sucker type under-chassis , super shockproof, ideal for high speed operation.
Wide speed range:0-3000rpm/min, continuously variable motor and Brushless DC Motor are optional. Stable low speed, powerful high speed.
Shaking block convenient for replacement, stable and reliable, sturdy and durable eccentric bearing design.
Various shaking block adapters optional.(Suitable for Eppendorf Tube)



Specification

Orbit	4mm
Shaking mode	circle
Operation mode	Continuous running/ Short Mix
Speed Range	100 ~ 3000rpm
Voltage	AC220V/AC110V,50/60Hz
Power	60W



Order information

Cat.No.	Part.No.	Specification
8011690	TM-Mivot	Vortex Mixer 220V/50Hz(with standard head)
8011690-1	MT-S	Standard head. Suit for 1.5mlX8 centrifuge tubes
8011690-2	MT-A	Foam tube holder for 15mlX8 & 10mlX8
8011690-3	MT-B	50mlX6/Foam tube holder for 50mlX6
8011690-4	MT-C	Plate holder platform. For all standard plates
8011690-5	MT-D	Plate adapter suitable for less than 120mm diameter tube or container .
8011690-6	MT-E	Tube holder platform. For 1.5ml/2.0ml tubes x 12
8011690-7	MT-F	Tube holder platform. For 15ml tubes x 4
8011690-8	MT-G	Tube holder platform. For 50ml tubes x 2